

## Technical information

### Retanning

### Syntans & Auxiliaries

Rockytan RE-540 is a copolymer retanning agent based on acrylic monomers. It plays a very important role in filling of the loose bellies. Rockytan RE-540 helps to improve buffing characteristic on suede leathers also.

### Properties

Appearance: Opaque cream viscose liquid

Nature: Acrylic

Activity %:  $40 \pm 1$

Moisture %:  $60 \pm 1$

Ionity: Anionic

pH (1:10 solution):  $4 \pm 1$

Safety: According to our best experience, it hasn't any harmful effect on health. for more information refer to MSDS

Storage Conditions: Store in a cool, dry, (15-25°C), out of direct sunlight.

Packing: 100,200 Kg's PE open mouth drums

# Rockytan RE-540

**H.S Code:3202.10**

### Applications & Recommendation

Rockytan RE-540 makes leather, very soft and full fill.

Rockytan RE-540 is a very good retanning agent for all types of

leather. It has also a good light fastness property in white crust. Before retanning, the leathers must be neutralized well. Due to low PH value of the product, it can be used also at the top stage for fixing other chemicals and better feel. The dosage of consumption depends on the type of leather and varies between 1-4% (based on the shaved weight).

After Neutralization:

80% Water 35 °C

X% Dye 45-60'

1-4% Rockytan RE-540 30'

+ Other retanning agents

Or after fatliquoring:

1-2% Rockytan RE-540 30'

**NOTE:** According to our best knowledge and technical experiments, the above data is true and accurate. Regarding to variety of consumption procedures, it is recommended to evaluate the information before use.

No. 47, South Iranshahr,  
Tehran-IRAN  
Phone: +98 21 8884 3227  
Fax: +98 21 8884 7639

[www.rockchemie.com](http://www.rockchemie.com)

[info@rockchemie.com](mailto:info@rockchemie.com)

