
Technical Data Sheet

Wood, Carpentry, MDF & etc.

ADHARENT WA 3211

Vinyl Acetate Adhesive

Description

This kind of adhesive is produced based on vinyl acetate homopolymer emulsion, and there is no filler is used in its formation.

If **ADHARENT WA 3211** is used to paste two wooden parts, that connection will be so strong and irrefrangible that there would not be any way to detach them but breaking. So it is used in a diverse range of industries.

25°C for maximum 12 months.

- Freezing and direct sun light must be avoided.
- This adhesive is inflammable.
- In case eye contact, wash the eyes with plenty of water.

Typical Properties

| Item | Result |
|------------------------------------|----------------------|
| Appearance | Milky White Emulsion |
| Solid Content (%) | 26±1 |
| Brookfield Viscosity @25°C (cp) | 25000-30000 |
| PH | 5-6 |
| MFFT(°C) | 5 |

Applications

This product is used in MDF industries, carpentry, furniture, office supplies and duplications.

Product Handling, Storage and Shelf Life

- To ensure safe storage of this emulsion, containers should be well sealed to prevent water evaporation and skin forming.
- The product must be stored between 5-

Address: No. 47, South Iranshahr, Tehran, IRAN.

Phone: +98 21 8884 3227

Fax: +98 21 8884 7639

Website: www.rockchemie.com

Email: info@rockchemie.com

NOTE: To the best of our knowledge and technical experiments, the above data is true and accurate. Given the variety of consumption fields, it is recommended to evaluate the information before use.

