
Technical information

Beamhouse

Bating Agent

Rockenzyme 7500-L is a protease alkaline bating agent which contains ammonium salts and buffers. Rockenzyme 7500-L is suited for all kinds of pelts. By applying Rockenzyme 7500-L the grain clarity and smoothness will be improved and all excess proteins will be dissolved and removed from the hides and skins.

Properties:

Appearance: Cream powder

Nature: Protease alkaline enzyme

Solid %: 100

Activity %: 1500 Ivu

pH(1:10 solution): Neutral

Safety: Refer to MSDS

Storage Condition: Store in a cool, dry, well-ventilated area (15-25°C)

Packing: 25 Kg's PE bags

Rockenzyme 7500-L

H.S Code:3202.90

Applications & Recommendation

Rockenzyme 7500-L is very effective at temperature of 33 - 37 °C and PH Value 8.3. Used quantity is different based on the type of pelt and degree of required effect.

The recommendation for use is :

0.5-1.0% (Pelt wt.) Cow

0.4-0.6% (" ") Sheep

0.4-1.3% (" ") Goat

1.5-2.0% (" ") Buffalo

After liming and fleshing

300% Water 25°C 15' drain

300% Water 30°C 15' drain

100% Water 37°C

0.1% Rockol 642

X% Rockenzyme 7500-L 30-60' drain

Check bating process & Drain

300% Water 37°C 15' drain

300% Water 25°C 15' drain

NOTE: According to our best knowledge and technical experiments, the above data is true and accurate. Regarding to variety of consumption procedures, it is recommended to evaluate the information before use.

No. 47, South Iranshahr,
Tehran RAN

Phone: +98 21 8884 3227

Fax: +98 21 8884 7639

www.rockchemie.com

nfo@rockchemie.com

