
Technical information

Paint industry

Antifoam agent

Bertafoam 1601

BERTAFOAM 1601 is a fully Non-Silicone defoamer based on mineral oils which is designed to be used in many industries such as Emulsion paints, Agricultural sprays, Printing colors & inks, Adhesives, Floor cleaning compounds, Paper coatings and Effluent systems.

Applications & Recommendation

BERTAFOAM 1601 can be used as received or may be prediluted in water. The diversity in application of **BERTAFOAM1601** makes listing of specific concentration of all the uses very difficult. It may be effectively used in:

Effluent and wash system at 10 ppm

Paper coatings at 0.2 %

Floor cleaning compounds at 0.1 – 0.3 %

Properties:

Appearance	: Opaque tan liquid
Activity	: 100%
Specific Gravity (25°C)	: 0.85
Brookfield Viscosity (25°C)	: 200-1000 cps
Packing	: 100 kg drums

Advantages

1. Provides rapid foam knockdown.
2. Dispersible in water to give emulsions of moderate stability.
3. High efficiency for maximum economy.
4. Effective in acidic or alkaline systems.
5. Long lasting efficiency.
6. Stable under adverse pH conditions.
7. Non silicone based.

No. 47, South Iranshahr,
Tehran-IRAN
Phone: +98 21 8884 3227-8
Fax: +98 21 8884 3229
www.rockchemie.com
info@rockchemie.com

NOTE: According to our best knowledge and technical experiments, the above data is true and accurate. Regarding to variety of consumption procedures, it is recommended to evaluate the information before use.

